

ORDERING
INFORMATION

Sample code explained: UFMc - CTm - PS3010 H - RS2 - B

UFM	Transducer Model	
	UFMc	: Clamp on Type
	UFMi	: Insertion Type
PS3010 H	Transmitter Model	
	PS3010 H	: Handheld
	PS3030 W	: Wall Mounting
CTm	Line Size	
	Sensor for Clamp on Type	
	CTm	: DN50 to DN250
	CT/	: DN300 to DN2000
	Sensor for Insertion without Spool	
	CT/ Probe : DN50 - DN2000	
	Sensor for Insertion with Spool	
	DN50 : 2"	DN600 : 24"
	DN65 : 2 ½"	DN700 : 28"
	DN80 : 3"	DN750 : 30"
RS2	Communication Facility	
	RS4	: Rs485
	RS2	: RS232
B	Power Supply	
	3	: 12 – 24 V DC
	U	: 85 – 264 V AC
	B	: Battery Operated

ULTRASONIC FLOW METER TYPE

Installation of Clamp-On Type
Ultrasonic Flow Meter



Installation of Insertion
Type Ultrasonic Flow Meter



Due to continuous development specifications are subject to change without prior notice.



Manas Microsystems Pvt.Ltd.

EL 54, Electronic Zone,
J-block, MIDC Bhosari,
Pune 411026.
Maharashtra, India.

Tel: 8484039026
Mob: +91 77220 34924 / 74200 99054
mktg@manasmicro.com
www.manasmicro.com

We are certified with:

ISO/IEC 17025:2017 | ISO 9001:2015 | ISO 14001:2015 | OHSAS 45001:2018



FC-COU-1NU-01_2 | UFM-1

www.manasmicro.com

ULTRASONIC
FLOW METER



UFMi and UFMc

We are certified with

ISO/IEC 17025:2017 | ISO 9001:2015
ISO 14001:2015 | OHSAS 45001:2018



ULTRASONIC FLOW METER

UFMc and UFMi

INTRODUCTION

Manas Microsystems is one of India's top Ultrasonic Flow Meter manufactures and suppliers. A comprehensive range of Ultrasonic Flow Meters is available from Manas, including Clamp-on Type Ultrasonic Flow Meters, and Insertion Ultrasonic Flow Meters, Portable Ultrasonic Water Flow Meter and Handheld Ultrasonic Water Flow Meter. These meters work on transit time principle.

When the Ultrasound wave passes through the liquid the component of liquid velocity is added to ultrasound velocity.

By careful measurement of the Time required by the sound wave to reach the other end of the diameter, one can calculate accurately the water velocity. By knowing the velocity, the volumetric flow rate can be calculated.

For the volumetric metering of water, ultrasonic flow meters have been used in businesses and markets for a long time. The transit time meter is used for clear liquids of liquids having very low levels of undissolved solids.

PRINCIPLE OF OPERATION

For measuring the flow of the medium, two ultrasonic pulses are sent through the medium, one in the flow direction and another in the opposite direction. The transit time of the two pluses is then measured. The transit time difference between these two pluses gives the average flow velocity on the propagation path of the Ultrasonic Signals. This can be used to obtain the average flow velocity on the cross-section of the pipe, which is proportional to the volumetric flow.

FEATURES

- Sizes available for 2" to 80" (DN50 -DN2000)
- The meter contains no moving parts and fast response to flow transit
- Highly accurate and reliable
- Isolated 4-20 mA output proportional to flow rate
- No need to cut the pipe or stop water, easy installation

TRANSDUCER TYPES

Clamp on Type

The transducers are clamped on the outside surface of the closes pipe.



Insertion Type

The transducers are inserted in the surface of the closes pipe.




Full Bore Type

The transducers are aligned diagonally on the surface of the closes pipe.



TRANSIT TIME PRINCIPLE



TECHNICAL SPECIFICATION OF TRANSDUCER

Specification	Clamp on		Insertion
	Ctm	Ctl	UFMi
Applicable Line Size	DN50 to DN250	DN300 to DN2000	DN50 to DN2000
Accuracy	±2%	±2%	±2%
Protection	IP68	IP68	IP68
Pressure	PN16	PN16	PN16
Medium Temperature	-30 °Cto 90 °C	-30 °C to 90 °C	-30 °C to 160 °C
Installation	No need to cut the pipe or stop water, easy installation		No need to cut the pipe or stop water
Feasibility	Not applicable to pipes of cement of glass steel material which are not ultrasound-conductive		Suitable for pipes where welding is available
Thickness	No Limitation		For pipe having thickness less than 20mm

TECHNICAL SPECIFICATION OF TRANSDUCER

Specification	PS3010 H	PS3030 W
Fluid Type	Clear Water	Clear Water
Mounting	Handheld	Wall Mounting
Protection	NA	IP65
Housing	ABS	Aluminum
Velocity Range	0~±7 m/s	0~±7 m/s
Pipe Material	Carbon Steel, Stainless Steel, Cast Iron, Copper and PVC	Carbon Steel, Stainless Steel, Cast Iron, Copper and PVC
Power Supply	Built in Rechargeable Ni-MH Batteries, 12 Hours Operation (with Charger)	85-264 V AC; 12-24 V DC
Display	4 X 16 Character with back light	2 X 20 English letters with back light
Communication	RS232 Interface support MODBUS	RS485 Interface support MODBUS
Output	NA	4-20mA
Accuracy	±2%	±2%